





**Elmo  
Rietschle**

# G-BH 1 N

## Data sheet 2BH1 600


Side channel blower with NEMA Premium motor



### Performance curves

#### Vacuum operation (acfm)

#### Pressure operation (scfm)



The performance curves are based on air at a temperature of 59 F and an atmospheric pressure of 29.92 inch Hg with a tolerance of  $\pm 10\%$ . The total Suction capacity relates to inlet conditions. Pressure capacity relates to atmospheric conditions. For other conditions please contact Elmo Rietschle.

Every G-BH blower can be used either for vacuum or pressure in continuous operation over the total performance curve range. The standard motors have a protection category of IP 55 and insulation class F. These blowers are UL and CSA approved.

## Selection and ordering data

Type										
No.	Fre- quency	Rated			Max. differential <sup>2)</sup> pressure		sound press. level <sup>3)</sup>	Efficiency class <sup>4)</sup>	Weight approx.	Order No.
		Voltage <sup>1)</sup>	Current	Power	Vacuum	Pressure				
		Hz	V	A	hp	inch H <sub>2</sub> O				
<b>IE3 3- 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)</b>										
1	50	190-210 Δ	6,9 Δ	2,3	-52	48	69	IE3	77	2BH1600-1AK01
	60	190-210 YY / 380-420 Y	7,8 YY / 3,9 Y	2,7	-44	44	72	IE3		
	60	200 YY	7,8 YY	2,7	-44	44	72	NP		
2	50	190-210 Δ	9,9 Δ	3,4	-80	76	64	IE3	86	2BH1600-1AK11
	60	190-210 YY / 380-420 Y	12,0 YY / 6,0 Y	4,0	-76	72	70	IE3		
	60	200 YY	12,0 YY	4,0	-76	72	70	NP		
3	50	190-210 Δ	13,3 Δ	4,6	-112	112	71	IE3	97	2BH1600-1AK21
	60	190-210 YY / 380-420 Y	15,2 YY / 7,6 Y	5,4	-108	108	74	IE3		
	60	200 YY	15,2 YY	5,4	-108	108	74	NP		
4	50	190-210 Δ	17,1 Δ	6,2	-116	145	69	IE3	121	2BH1600-1AK31
	60	190-210 YY / 380-420 Y	19,6 YY / 9,8 Y	7,1	-132	145	71	IE3		
	60	200 YY	19,6 YY	7,1	-132	145	71	NP		
<b>IE3 3- 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)</b>										
1	50	220-240 Δ / 380-420 Y	6,0 Δ / 3,45 Y	2,3	-52	48	69	IE3	77	2BH1600-1AK06
	60	220-240 YY / 440-480 Y	6,8 YY / 3,4 Y	2,7	-44	44	72	IE3		
	60	230 YY / 460 Y	6,8 YY / 3,4 Y	2,7	-44	44	72	NP		
2	50	220-240 Δ / 380-420 Y	8,6 Δ / 5,0 Y	3,4	-80	76	64	IE3	86	2BH1600-1AK16
	60	220-240 YY / 440-480 Y	10,4 YY / 5,2 Y	4,0	-76	72	70	IE3		
	60	230 YY / 460 Y	10,4 YY / 5,2 Y	4,0	-76	72	70	NP		
3	50	220-240 Δ / 380-420 Y	11,6 Δ / 6,7 Y	4,6	-112	112	71	IE3	97	2BH1600-1AK26
	60	220-240 YY / 440-480 Y	13,2 YY / 6,6 Y	5,4	-108	108	74	IE3		
	60	230 YY / 460 Y	13,2 YY / 6,6 Y	5,4	-108	108	74	NP		
4	50	220-240 Δ / 380-420 Y	14,9 Δ / 8,6 Y	6,2	-116	145	69	IE3	121	2BH1600-1AK36
	60	220-240 YY / 440-480 Y	17,0 YY / 8,5 Y	7,1	-132	145	71	IE3		
	60	230 YY / 460 Y	17,0 YY / 8,5 Y	7,1	-132	145	71	NP		
<b>IE3 3- 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)</b>										
1	50	475-525 Y	2,76 Y	2,3	-52	48	63	IE3	97	2BH1600-1AQ03
	60	550-600 Y	2,72 Y	2,7	-44	44	68	NP		
2	50	475-525 Y	4,0 Y	3,4	-80	76	64	IE3	108	2BH1600-1AQ13
	60	550-600 Y	4,1 Y	4,0	-76	72	70	NP		
3	50	475-525 Y	5,4 Y	4,6	-112	112	71	IE3	95	2BH1600-1AQ23
	60	550-600 Y	5,3 Y	5,4	-108	108	74	NP		
4	50	475-525 Y	6,9 Y	6,2	-116	145	69	IE3	139	2BH1600-1AQ33
	60	550-600 Y	6,8 Y	7,1	-132	145	71	NP		
<b>IE3 3- 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)</b>										
1	50	380-420 Δ / 660-725 Y	3,45 Δ / 2,00 Y	2,3	-52	48	63	IE3	97	2BH1600-1AQ07
	60	440-480 Δ	3,40 Δ	2,7	-44	44	68	IE3		
	60	460 Δ	3,40 Δ	2,7	-44	44	68	NP		
2	50	380-420 Δ / 660-725 Y	5,0 Δ / 2,90 Y	3,4	-80	76	64	IE3	108	2BH1600-1AQ17
	60	440-480 Δ	5,2 Δ	4,0	-76	72	70	IE3		
	60	460 Δ	5,2 Δ	4,0	-76	72	70	NP		
3	50	380-420 Δ / 660-725 Y	6,7 Δ / 3,85 Y	4,6	-112	112	71	IE3	95	2BH1600-1AQ27
	60	440-480 Δ	6,6 Δ	5,4	-108	108	74	IE3		
	60	460 Δ	6,6 Δ	5,4	-108	108	74	NP		
4	50	380-420 Δ / 660-725 Y	8,6 Δ / 5,0 Y	6,2	-116	145	69	IE3	139	2BH1600-1AQ37
	60	440-480 Δ	8,5 Δ	7,1	-132	145	71	IE3		
	60	460 Δ	8,5 Δ	7,1	-132	145	71	NP		

- 1) In case of variable frequency drive operation the standard motor insulation system is suitable for VFD input voltages up to 500 V.
- 2) Relief valves available for limiting differential pressure.
- 3) Surface sound pressure levels are according to EN ISO 3744, measured with an equivalent unit at a distance of 1 m. The pump is throttled to an average suction pressure, with piping connected, but no relief valves fitted, tolerance ±3 dB (A).
- 4) The motors according to NEMA MG1-12. NP=NEMA Premium; NEMA Premium includes IE3.

All G-BH blowers conform to the 2006/42/EC (machinery) and 2006/95/EC (low voltage) directives and the EN 60034 norm "Rotating electrical machines".

Service factor (SF) and motor efficiency according NEMA MG1-12.

Voltage tolerances for three phase motors are +/-10%.

The frequency tolerance is +/- 2% maximum.

Voltage range		Efficiency <sup>4)</sup>	c  us	60 Hz	
50 Hz	60Hz			2BH1...-1.	□ . □
<b>3-</b>					
200 VΔ	200 V YY / 230 VΔ / 400 VY		•	K	1
190-210 VΔ	190-210 VYY / 220-240 VΔ / 380-420VY	IE3			
200 V YY / 230 VΔ / 400 VY	230 V YY / 460 VY		•	K	6
190-210 VYY / 220-240 VΔ / 380-420VY	220-240 VYY / 440-480VY	IE3			
475-525 V Y	550-600 V Y		•	Q	3
475-525 VΔ	550-600 VΔ		•	Q	5
400 VΔ / 690 V Y	460 VΔ		•	Q	7

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given does not constitute an obligation from our side to deliver as shown.

Elmo Rietschle is a brand of Gardner Denver  
  
 Your Ultimate Source for Vacuum and Pressure

**Gardner Denver Deutschland GmbH**  
 Industriestraße 26  
 97616 Bad Neustadt - Germany  
 Tel.: +49 9771 6888-0  
 Fax: +49 9771 6888-4000  
 www.elmorietschle.com

**Gardner Denver, Inc.**  
 1800 Gardner Expressway  
 Quincy, IL 62305  
 Tel: 866-249-2275  
 Fax: 217-221-8780  
 www.elmorietschle.com