

G-BH 1 N

Data sheet 2BH1 690


Side channel blower with NEMA Premium motor



Performance curves

Vacuum operation (acfm)

Pressure operation (scfm)



The performance curves are based on air at a temperature of 59 F and an atmospheric pressure of 29.92 inch Hg with a tolerance of $\pm 10\%$. The total Suction capacity relates to inlet conditions. Pressure capacity relates to atmospheric conditions. For other conditions please contact Elmo Rietschle.

Every G-BH blower can be used either for vacuum or pressure in continuous operation over the total performance curve range. The standard motors have a protection category of IP 55 and insulation class F. These blowers are UL and CSA approved.

Selection and ordering data

Type										
No.	Fre- quency Hz	Rated			Max. differential ²⁾ pressure		sound press. level ³⁾ dB(A)	Efficiency class ⁴⁾	Weight approx. lbs	Order No.
		Voltage ¹⁾	Current	Power	Vacuum	Pressure				
		V	A	hp	inch H ₂ O					
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)										
1	50	190-210 Δ	9,9 Δ	3,4	-80	68	64	IE3	86	2BH1690-1AK11
	60	190-210 YY / 380-420 Y	12,0 YY / 6,0 Y	4,0	-76	68	70	IE3		
	60	200 YY	12,0 YY	4,0	-76	68	70	NP		
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)										
1	50	220-240 Δ / 380-420 Y	8,6 Δ / 5,0 Y	3,4	-80	68	64	IE3	86	2BH1690-1AK16
	60	220-240 YY / 440-480 Y	10,4 YY / 5,2 Y	4,0	-76	68	70	IE3		
	60	230 YY / 460 Y	10,4 YY / 5,2 Y	4,0	-76	68	70	NP		
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)										
1	50	475-525 Y	4,0 Y	3,4	-80	68	64	IE3	108	2BH1690-1AQ13
	60	550-600 Y	4,1 Y	4,0	-76	68	70	NP		
IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL 1450 (certificate number E225239)										
1	50	380-420 Δ / 660-725 Y	5,0 Δ / 2,90 Y	3,4	-80	68	64	IE3	108	2BH1690-1AQ17
	60	440-480 Δ	5,2 Δ	4,0	-76	68	70	IE3		
	60	460 Δ	5,2 Δ	4,0	-76	68	70	NP		

- 1) In case of variable frequency drive operation the standard motor insulation system is suitable for VFD input voltages up to 500 V.
- 2) Relief valves available for limiting differential pressure.
- 3) Surface sound pressure levels are according to EN ISO 3744, measured with an equivalent unit at a distance of 1 m. The pump is throttled to an average suction pressure, with piping connected, but no relief valves fitted, tolerance ±3 dB (A).
- 4) The motors according to NEMA MG1-12. NP=NEMA Premium; NEMA Premium includes IE3.

All G-BH blowers conform to the 2006/42/EC (machinery) and 2006/95/EC (low voltage) directives and the EN 60034 norm "Rotating electrical machines".

Service factor (SF) and motor efficiency according NEMA MG1-12.

Voltage tolerances for three phase motors are +/-10%.

The frequency tolerance is +/- 2 % maximum.

Motor for alternate voltages

Voltage range		Efficiency ⁴⁾	cULus 60 Hz	2BH1...-1. □ . □	
50 Hz	60Hz				
3~					
200 VΔ	200 V YY / 230 VΔ / 400 VY		•		1
190-210 VΔ	190-210 VYY / 220-240 VΔ / 380-420VY		•	K	
200 V YY / 230 VΔ / 400 VY	230 V YY / 460 VY		•		6
190-210 VYY / 220-240 VΔ / 380-420VY	220-240 VYY / 440-480VY		•	K	
475-525 V Y	550-600 V Y		•	Q	3
475-525 VΔ	550-600 VΔ		•	Q	5
400 VΔ / 690 V Y	460 VΔ		•	Q	7

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given does not constitute an obligation from our side to deliver as shown.

Elmo Rietschle is a brand of Gardner Denver

**Gardner
Denver**

Your Ultimate Source for Vacuum and Pressure

Gardner Denver Deutschland GmbH

Industriestraße 26
97616 Bad Neustadt - Germany

Tel.: +49 9771 6888-0
Fax: +49 9771 6888-4000

www.elmorietschle.com

Gardner Denver, Inc.

1800 Gardner Expressway
Quincy, IL 62305

Tel: 866-249-2275
Fax: 217-221-8780

www.elmorietschle.com