



# Elmo Rietschle

## G-BH 1 N

### Data sheet 2BH7 620-0A


Side channel blower with NEMA Premium motor



#### Performance curves

##### Vacuum operation (acfm)

##### Pressure operation (scfm)



The performance curves are based on air at a temperature of 59 F and an atmospheric pressure of 29.92 inch Hg with a tolerance of ± 10 %. The total Suction capacity relates to inlet conditions. Pressure capacity relates to atmospheric conditions. For other conditions please contact Elmo Rietschle.

Every G-BH blower can be used either for vacuum or pressure in continuous operation over the total performance curve range. The standard motors have a protection category of IP 55 and insulation class F. These blowers are UL and CSA approved.

## Selection and ordering data

Type										
No.	Fre- quency	Rated			Max. differential <sup>2)</sup> pressure		sound press. level <sup>3)</sup>	Efficiency class <sup>4)</sup>	Weight approx.	Order No.
		Voltage <sup>1)</sup>	Current	Power	Vacuum	Pressure				
		Hz	V	A	hp	inch H <sub>2</sub> O				
<b>IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL (certificate number E489378)</b>										
1	50	190-210 Δ	13,3 Δ	4,6	-185	201	67	IE3	130	2BH7620-0AK21-1
	60	190-210 YY / 380-420 Y	15,2 YY / 7,6 Y	5,4	-209	185	71	IE3		
	60	200 YY	15,2 YY	5,4	-209	185	71	NP		
2	50	190-210 Δ	17,1 Δ	6,2	-209	281	67	IE3	146	2BH7620-0AK41-1
	60	190-210 YY / 380-420 Y	19,6 YY / 9,8 Y	7,1	-229	265	71	IE3		
	60	200 YY	19,6 YY	7,1	-229	265	71	NP		
3	50	190-210 Δ	23,5 Δ	8,4	-209	361	68	IE3	163	2BH7620-0AK71-1
	60	190-210 YY / 380-420 Y	27,6 YY / 13,8 Y	9,8	-229	381	72	IE3		
	60	200 YY	27,6 YY	9,8	-229	381	72	NP		
<b>IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL (certificate number E489378)</b>										
1	50	220-240 Δ / 380-420 Y	11,6 Δ / 6,7 Y	4,6	-185	201	67	IE3	130	2BH7620-0AK26-1
	60	220-240 YY / 440-480 Y	13,2 YY / 6,6 Y	5,4	-209	185	71	IE3		
	60	230 YY / 460 Y	13,2 YY / 6,6 Y	5,4	-209	185	71	NP		
2	50	220-240 Δ / 380-420 Y	14,9 Δ / 8,6 Y	6,2	-209	281	67	IE3	146	2BH7620-0AK46-1
	60	220-240 YY / 440-480 Y	17,0 YY / 8,5 Y	7,1	-229	265	71	IE3		
	60	230 YY / 460 Y	17,0 YY / 8,5 Y	7,1	-229	265	71	NP		
3	50	220-240 Δ / 380-420 Y	20,4 Δ / 11,8 Y	8,4	-209	361	68	IE3	163	2BH7620-0AK76-1
	60	220-240 YY / 440-480 Y	24,0 YY / 12,0 Y	9,8	-229	381	72	IE3		
	60	230 YY / 460 Y	24,0 YY / 12,0 Y	9,8	-229	381	72	NP		
<b>IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL (certificate number E489378)</b>										
1	50	500 Y	5,4 Y	4,6	-185	201	67	IE3	130	2BH7620-0AQ23-1
	60	575 Y	5,3 Y	5,4	-209	185	71	NP		
2	50	500 Y	6,9 Y	6,2	-209	281	67	IE3	146	2BH7620-0AQ43-1
	60	575 Y	6,8 Y	7,1	-229	265	71	NP		
3	50	500 Y	9,5 Y	8,4	-209	361	68	IE3	163	2BH7620-0AQ73-1
	60	575 Y	9,6 Y	9,8	-229	381	72	NP		
<b>IE3 3~ 50/60 Hz, IP55, Insulation material class F, UL (certificate number E489378)</b>										
1	50	380-420 Δ / 660-725 Y	6,7 Δ / 3,85 Y	4,6	-185	201	67	IE3	130	2BH7620-0AQ27-1
	60	440-480 Δ	6,6 Δ	5,4	-209	185	71	IE3		
	60	460 Δ	6,6 Δ	5,4	-209	185	71	NP		
2	50	380-420 Δ / 660-725 Y	8,6 Δ / 5,0 Y	6,2	-209	281	67	IE3	146	2BH7620-0AQ47-1
	60	440-480 Δ	8,5 Δ	7,1	-229	265	71	IE3		
	60	460 Δ	8,5 Δ	7,1	-229	265	71	NP		
3	50	380-420 Δ / 660-725 Y	11,8 Δ / 6,8 Y	8,4	-209	361	68	IE3	163	2BH7620-0AQ77-1
	60	440-480 Δ	12,0 Δ	9,8	-229	381	72	IE3		
	60	460 Δ	12,0 Δ	9,8	-229	381	72	NP		

2) Relief valves available for limiting differential pressure.

3) Surface sound pressure levels are according to EN ISO 3744, measured with an equivalent unit at a distance of 1 m. The pump is throttled to an average suction pressure, with piping connected, but no relief valves fitted, tolerance ±3 dB (A).

4) The motors according to NEMA MG1-12. NP=NEMA Premium; NEMA Premium includes IE3.

All G-BH blowers conform to the 2006/42/EC (machinery) and 2006/95/EC (low voltage) directives and the EN 60034 norm "Rotating electrical machines".

Service factor (SF) and motor efficiency according NEMA MG1-12.

Voltage tolerances for three phase motors are +/-10%.

The frequency tolerance is +/- 2 % maximum.

## Motor for alternate voltages

Voltage range		Efficiency <sup>4)</sup>	60 Hz	2BH7...-... □ . □
50 Hz	60Hz			
<b>3~</b>				
200 VΔ	200 V YY / 230 VΔ / 400 VY		•	K 1
190-210 VΔ	190-210 VYY / 220-240 VΔ / 380-420VY		•	K 1
200 VΔ / 230 VΔ / 400 VY	230 V YY / 460 VY		•	K 6
190-210 VYY / 220-240 VΔ / 380-420VY	220-240 VYY / 440-480VY		•	K 6
475-525 V Y	550-600 V Y		•	Q 3
475-525 VΔ	550-600 VΔ		•	Q 5
400 VΔ / 690 V Y	460 VΔ		•	Q 7

Changes in particular of the quoted performance curve, data and weights may occur without prior notice. The data given does not constitute an obligation from our side to deliver as shown.

Elmo Rietschle is a brand of Gardner Denver

**Gardner  
Denver**

Your Ultimate Source for Vacuum and Pressure

**Gardner Denver Deutschland GmbH**

Industriestraße 26  
97616 Bad Neustadt - Germany

Tel.: +49 9771 6888-0  
Fax: +49 9771 6888-4000

www.elmorietschle.com

**Gardner Denver, Inc.**

1800 Gardner Expressway  
Quincy, IL 62305

Tel: 866-249-2275  
Fax: 217-221-8780

www.elmorietschle.com