

125-200 HP ROTARY SCREW COMPRESSORS

# Electra Saver® II

## A Legendary Compressor

The engineering ingenuity of Gardner Denver began in 1859. For over 150 years, our compressed air products have been a dependable resource for meeting the world's most demanding and everchanging industrial needs. A legend in its own right, the Electra Saver® II has been carrying on that legacy for over 30 years.

#### Bigger is Better

Featuring super-sized bearings and up to 40% larger airends than the competition, the Electra Saver® II is not only bigger, it is better. The larger airends, running at slower speeds, maximize efficiency and reduce mechanical wear and tear, while the permanent alignment of the airend and motor ensure maximum coupling and bearing life.

## Premium Package Features

Our quality compressors come standard with a cast iron, EISA premium efficiency motor containing more winding material than any other motor. Electra Saver® II machines utilize seamless stainless steel control lines and tubing for superior lubricant circulation. Considering an inlet filter is no place to cut corners, we use a heavy duty, two-stage high efficiency inlet filter which extends lubricant life by almost 20%. In addition, our air/oil separator has twice the surface area of conventional separators providing better separation, longer life, and the lowest carry-over in the industry. Whether it's an unenclosed or quiet enclosed configuration the Electra Saver® II redefines serviceability with easy access to all service points.



#### ELECTRA SAVER II 125-200 HP ROTARY SCREW COMPRESSOR

MODEL	DRIVE MOTOR		50 Hz				60 Hz							
			NOMINAL PRESSURE		FAD		NOMINAL PRESSURE		FAD		NOISE LEVEL <sup>1</sup>	WEIGHT		DIMENSIONS L × W × H
	НР	KW	PSIG	BAR	ACFM	M³/MIN	PSIG	BAR	ACFM	M³/MIN	DB(A)	LBS	KG	IN. (MM)
ST-125	125	90	100 125 150 175 200	6.9 8.6 10.3 12.0 13.8	610 500 428 N/A N/A	17.28 14.16 12.12 N/A N/A	100 125 150 175 200	6.9 8.6 10.3 12.0 13.8	620 537 485 343.5 339.5	17.56 15.21 13.74 9.73 9.62	88	4804	2179	
ST-150	150	110	100 125 150 175 200	6.9 8.6 10.3 12.0 13.8	734 637 632 N/A N/A	20.79 18.05 17.90 N/A N/A	100 125 150 175 200	6.9 8.6 10.3 12.0 13.8	750 618 529 481.5 477	21.25 17.51 14.99 13.64 13.51	88	5111	2318	
ST-200*	200	150	100 125 150 175 200	6.9 8.6 10.3 12.0 13.8	N/A	N/A	100 125 150 175 200	6.9 8.6 10.3 12.0 13.8	750 744 732 713 582	21.25 21.08 20.74 20.20 16.49	88	5479	2485	
ST-200	200	150	100 125	6.9 8.6	817 701	23.14 19.86	100 125	6.9 8.6	1000 875	28.33 24.79	88	6328	2870	

<sup>\* 100, 110, 125</sup> psig available as field set option only.

## Electra Saver® II Features (125-200 HP)

- Direct drive, oil flooded, single stage rotary screw air compressor
- AEON 9000SP
- Air and water-cooled
- AirSmart™ microprocessor controller
- Oil cooler/aftercooler:
   Air-cooled models heavy duty radiator-type with thermally controlled, totally enclosed fan motor; Water-cooled models shell and tube heat exchanger
- cULus listed and CSA approved enclosed control panels

- Enclosure: unenclosed standard; enclosed/quiet enclosed - optional
- Modulating inlet valve control
- Package mounted moisture separator/trap
- Wye-delta starter
- NEMA 4 electrical enclosure
- ODP main motor; optional TEFC main motor
- ASME coded oil reservoir
- Thermostatic thermal mixing valve
- Stainless steel control lines

- Minimum pressure discharge check valve
- Optional AirSmart communications module
- Optional remote mounted air-cooled cooler
- Optional seacoast (air-cooled) or salt water (water-cooled) cooler
- Voltage: 200 / 230 / 460 / 575 V(3 phase only) varies by model



Gardner Denver, Inc.

1800 Gardner Expressway Quincy, IL 62305 866-440-6241

www.gardnerdenverproducts.com













<sup>1)</sup> Noise level, weights and dimensions are for unenclosed models.