

INDUSTRIAL | 5 HP ROTARY SCROLL AIR COMPRESSORS

Gardner Denver EnviroAire compressors provide the reliable, high quality compressed air that you've come to expect from Gardner Denver. EnviroAire compressors offer a wide selection of configurations and top-quality available options. Gardner Denver designed this series specifically for industrial and laboratory applications that require 100% oil-less air. Experience proven results with Gardner Denver-the leader in durability, reliability and efficiency.

Standard Equipment

- Continuous operation, 100% duty cycle
- 5 Micron industrial grade intake air filter
- ASME coded receiver
- Premium efficient TEFC motor
- Unique tip seal design
- Low sound levels and vibration
- Re-greasable bearings
- Integral cooling fan
- Easy accessibility for maintenance
- 1-Year package warranty
- 1-Year airend warranty

Available Options

- Tank Sizes—30, 80, 120 or 240 gallon
 - Galvanized receiver
 - Vinyl (epoxy) lined receiver
- Electronic tank drain
- Mass. code fittings
- Starter
- High temp switch
- Vibration isolators
- Dryer options
 - Refrigerated dryer
 - Desiccant dryer



BARE AIREND

MODEL	DIMENSIONS L × W × H IN.	APPROX. SHIP WEIGHT LBS		
SC5	13.6 × 14.7 × 11.4	45		

SIMPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.			DIMENSIONS	APPROX. SHIP WEIGHT	116 PSI RATING		140 PSI RATING	
		L × W × H IN.	LBS	RPM	ACFM	RPM	ACFM	
5	Base	BENVS5	38 × 21 × 17	375	3100	13.9	2900	12.5
5	30	HENVS5-3	43 × 24 × 38	625	3100	13.9	2900	12.5
5	80	HENVS5-8	67 × 24 × 42	750	3100	13.9	2900	12.5
5	120	HENVS5-12	71 × 27 × 46	850	3100	13.9	2900	12.5

DUPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.		IDENTIFICATION	DIMENSIONS L × W × H	APPROX. SHIP WEIGHT	116 PSI RATING		140 PSI RATING	
	NUMBER	IN.	LBS	RPM	ACFM	RPM	ACFM	
5	Base	BENVSD	48 × 22 × 36.5	800	3100	27.8	2900	25
5	80	HENVS5D-8	65 × 26 × 61.5	1300	3100	27.8	2900	25
5	120	HENVS5D-12	69 × 27 × 65.5	1400	3100	27.8	2900	25
5	240	HENVS5D-24	86 × 33 × 71.5	1600	3100	27.8	2900	25

Simplex CFM values are doubled for duplex units. Duplex units have two motors and two pumps on one base/tank.

TRIPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.			DIMENSIONS	APPROX.	116 PSI RATING		140 PSI RATING	
	NUMBER	L × W × H IN.	SHIP WEIGHT LBS	RPM	ACFM	RPM	ACFM	
5	Base	BENVS5T	48 × 22 × 54.5	1200	3100	41.7	2900	37.5

Simplex CFM values are tripled for triplex units. Triplex units have three airends and three motors stacked on a common base.

QUADRAPLEX

MOTOR HP BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L × W × H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING		
				RPM	ACFM	RPM	ACFM	
5	Base	BENVS5Q	48 × 22 × 72	1800	3100	55.6	2900	50

Simplex CFM values are quadrupled for Quadraplex units. Quadraplex units have four airends and four motors stacked on a common base.



Gardner Denver, Inc.

1800 Gardner Expressway Quincy, IL 62305 866-440-6241 www.gardnerdenver.com/gdproducts

©2017 Gardner Denver, Inc. Printed in U.S.A. GLCS-ENV-IND-S5 1st Ed. 2/17





